

Signal Conditioning Product Grid

INPUT	TRANSMITTERS			ALARMS
	Output Loop Powered	DC Powered	AC Powered	
4-20mA Isolator	TT236 651T/652T	TT336 631T/632T 340i 330i	631T/632T 430i	
4-20mA Splitter	653T	633T	633T	
Current - wide ranging	TT236 250T-C1	TT336 611T/612T 811T-0500 350T-C1	450T-C1	811A/812A 811T-1500 260A 361A 461A
Voltage	TT237 (±10V) TT238 (±150V) 654T (±10V) 250T-Vx	TT337 (±10V) TT338 (±150V) 611T/612T (±100V) 811T-0500 (±100V) 350T-Vx	450T-Vx	361A 461A 811T-1500 811A/812A
Voltage - mV	TT233 TT236 655T/656T 250T-mVx 151T/155H - 115mV max	TT333 TT336 611T/612T 801T-0500 350T-mVx	450T-mVx	822A 801T-1500 801A 361A 461A
Thermocouple	TT233 (Isolated) 655T/656T 250T-TC1 250T-xL00 ST132 ST133 (Isolated) 151T/155H	TT333 (Isolated) 801T-0500 350T-TC1 350T-xL00	450T-TC1 450T-xL00	801T-1500 801A 822A
RTD	TT231 TT235 (Isolated) 657T/658T 250T-RBPx 250T-RBCx ST131 151T/155H	TT335 (Isolated) 801T-0500 350T-RBPx 350T-RBCx	450T-RBPx 450T-RBCx	801T-1500 801A 832A
Resistance	TT231 TT235 657T/658T 151T/155H	T335 801T-0500		801T-1500 801A 832A
Frequency	TT239 250T-FQ1	TT339 350T-FQ1 841T-0500	450T-FQ1	841T-1500
Potentiometer	TT234 250T-P	TT334 350T-P	450T-P	
Thermistor	TT234	TT334		
PWM Pulse-Width-Modulated	TT239	TT339		
Load Cell / Strain Gauge		851T-0500		851T-1500
AC Current with 5020-350	TT236 250T-CACX	TT336 611T 811T-0500 350T-CACX	450T-CACX	811A/812A
AC Voltage	250T-VAC	350T-VAC	450T-VAC	